

Polymer Matrix Composites: Materials Properties

CMH-17

COMPOSITE MATERIALS HANDBOOK



WICHITA STATE
UNIVERSITY



**NOT MEASUREMENT
SENSITIVE**

CMH-17-2H
Volume 2 of 6
FEBRUARY 2018

SUPERSEDING
CMH-17-2G
Volume 2 of 6
17 JUNE 2012

COMPOSITE MATERIALS HANDBOOK

POLYMER MATRIX COMPOSITES: MATERIALS PROPERTIES

VOLUME 2. Rev. H/Part A



CMH-17
COMPOSITE MATERIALS HANDBOOK

ISBN-Print 978-0-7680-9481-7

Copyright 2018 - Composite Materials Handbook – 17 (CMH-17). All rights reserved. Unauthorized duplication or distribution may violate the Copyright Laws of the United States and of other jurisdictions

TABLE OF CONTENTS

	Page
Foreword	ii
Summary of Changes	viii
 PART A	
Chapter 1 General Information	1-1
Chapter 2A Carbon Fiber Composites	2A-1
Appendix A1. MIL-HDBK-17A Data.....	A1-1
 PART B	
Chapter 2B Carbon Fiber Composites	2B-1
Chapter 3 Boron Fiber Composites	3-1
Chapter 4 Glass Fiber Composites	4-1
Chapter 5 Quartz Fiber Composites	5-1

TABLE

A1.1 U.S. Polymeric E-720E/7781 (ECDE/05-550) Fiberglass Epoxy	A1-6
A1.3 Hexcel F-161/7743(550) Fiberglass Epoxy	 A1-14
A1.4 Hexcel F-161/7781 (ECDE-1/0-550) Fiberglass Epoxy (26% resin)	 A1-24
A1.5 Hexcel F-161/7781 (ECDE-1/0-550) Fiberglass Epoxy (31% resin)	 A1-30
A1.6 Hexcel F-161/7781 (ECDE-1/0-550) Fiberglass Epoxy (36% resin)	 A1-36
A1.8 Narmco N588/7781 (ECDE-1/0-550) Fiberglass Epoxy	 A1-46
A1.40 Narmco N506/7781 (ECDE-1/0-A1100) Fiberglass Phenolic	 A1-56
A1.110 Narmco 5505 Boron-Epoxy (100%—0° Direction)	 A1-64
A1.111 Narmco 5505 Boron-Epoxy (0°-90° Crossply)	 A1-68

FIGURE

A1.1.1(a) Tensile stress-strain for E-720E/7781 fiberglass epoxy loaded in the 0° direction	 A1-7
A1.1.1(b) Tensile stress-strain for E-720E/7781 fiberglass epoxy loaded in the 90° direction	 A1-8
A1.1.2(a) Compressive stress-strain for E-720E/7781 fiberglass epoxy loaded in the 0° direction ...	A1-9
A1.1.2(b) Compressive stress-strain for E-720E/7781 fiberglass epoxy loaded in the 90° direction	 A1-10
A1.1.3 0°-90° rail shear for E-720E/7781 fiberglass	A1-11
A1.1.4 Poisson effects for E-720E/7781 fiberglass epoxy	 A1-12
A1.3.1(a) Tensile stress-strain for F-161/7743 fiberglass epoxy loaded in the 0° direction	 A1-15
A1.3.1(b) Tensile stress-strain for F-161/7743 fiberglass epoxy loaded in the 90° direction.....	A1-17
A1.3.2(a) Compressive stress-strain for F-161/7743 fiberglass epoxy loaded in the 0° direction....	A1-18
A1.3.2(b) Compressive stress-strain F-161/7743 fiberglass epoxy loaded in the 90° direction	A1-19
A1.3.3 0°-90° rail shear for F-161/7743 fiberglass epoxy	 A1-20
A1.3.4 Poisson effects for F-161/7743 fiberglass epoxy	 A1-21
A1.3.5 Voids vs. resin content and specific gravity for F-161/7743 fiberglass epoxy	 A1-22
A1.4.1(a) Tensile stress-strain for F-161/7781 fiberglass epoxy loaded in the 0° direction (26% resin)	A1.25
A1.4.1(b) Tensile stress-strain for F-161/7781 fiberglass epoxy loaded in the 90° direction (26% resin)	 A1-26

	Page
A1.4.2(a) Compressive stress-strain for F-161/7781 fiberglass epoxy loaded in the 0° direction (26% resin)	A1-27
A1.4.2(b) Compressive stress-strain for F-161/7781 fiberglass epoxy loaded in the 90° direction (26% resin)	A1-28
A1.4.4 Poisson effects for F-161/7781 fiberglass epoxy (26% resin)	A1-29
A1.5.1(a) Tensile stress-strain for F-161/7781 fiberglass epoxy loaded in the 0° direction (31% resin)	A1-31
A1.5.1(b) Tensile stress-strain for F-161/7781 fiberglass epoxy loaded in the 90° direction (31% resin)	A1-32
A1.5.2(a) Compressive stress-strain for F-161/7781 fiberglass epoxy loaded in the 0° direction (31% resin)	A1-33
A1.5.2(b) Compressive stress-strain for F-161/7781 fiberglass epoxy loaded in the 90° direction (31% resin)	A1-34
A1.5.4 Poisson effects for F-161/7781 fiberglass epoxy (31% resin)	A1-35
A1.6.1(a) Tensile stress-strain for F-161/7781 fiberglass epoxy loaded in the 0° direction (36% resin)	A1-37
A1.6.1(b) Tensile stress-strain for F-161/7781 fiberglass epoxy loaded in the 90° direction (36% resin)	A1-38
A1.6.2(a) Compressive stress-strain for F-161/7781 fiberglass epoxy loaded in the 0° direction (36% resin)	A1-39
A1.6.2(b) Compressive stress-strain for F-161/7781 fiberglass epoxy loaded in the 90° direction (36% resin)	A1-40
A1.6.3 Picture frame shear for F-161/7781 fiberglass epoxy (26%, 31%, 36% resin)	A1-41
A1.6.4 Poisson effects for F-161/7781 fiberglass epoxy (36% resin)	A1-42
A1.6.5 Voids vs. resin content and specific gravity for F-161/7781 fiberglass epoxy (26%, 31%, 36% resin)	A1-43
A1.6.6 Thickness vs. resin content for F-161/7781 fiberglass epoxy	A1-44
A1.8.1(a) Tensile stress-strain for N588/7781 fiberglass epoxy loaded in the 0° direction	A1-47
A1.8.1(b) Tensile stress-strain for N588/7781 fiberglass epoxy loaded in the 90° direction	A1-48
A1.8.2(a) Compressive stress-strain for N588/7781 fiberglass epoxy loaded in the 0° direction.....	A1-49
A1.8.2(b) Compressive stress-strain for N588/7781 fiberglass epoxy loaded in the 90° direction...	A1-51
A1.8.3 Rail shear for N588/7781 fiberglass epoxy	A1-52

	Page
A1.8.4 Poisson effects for N588/7781 fiberglass epoxy	A1-53
A1.8.5 Voids vs. resin content and specific gravity for N588/7781 fiberglass epoxy	A1-54
A1.40.1(a) Tensile stress-strain for N506/7781 fiberglass phenolic loaded in the 0° direction.....	A1-57
A1.40.1(b) Tensile stress-strain for N506/7781 fiberglass phenolic loaded in the 90° direction.....	A1-58
A1.40.2(a) Compressive stress-strain for N506/7781 fiberglass phenolic loaded in the 0° direction	A1-59
A1.40.2(b) Compressive stress-strain for N506/7781 fiberglass phenolic loaded in the 90° direction	A1-60
A1.40.3 0°-90° rail shear for N506/7781 fiberglass phenolic	A1-61
A1.40.4 Poisson effects for N506/7781 fiberglass phenolic	A1-62
A1.40.5 Voids vs. resin content and specific gravity for N506/7781 fiberglass phenolic	A1-63
A1.110.1 Tensile stress-strain for AVCO 5505 boron/epoxy (100% - 0° orientation/50.3% to 35% fiber volume) loaded in the 0° and 90° direction	A1-65
A1.110.2 Compressive stress-strain for AVCO 5505 boron/epoxy (100% - 0° orientation loaded in the 0° direction	A1-66
A1.110.3 Poisson effects for AVCO 5505 boron/epoxy (100% - 0° direction)	A1-67
A1.111.1(a) Tensile stress-strain for AVCO 5505 boron/epoxy (0°-90° crossply) loaded in the 0° direction	A1-69
A1.111.1(b) Tensile stress-strain for AVCO 5055 boron/epoxy (0°-90° crossply) loaded in the 45° direction	A1-70
A1.111.3 Poisson effects for AVCO 5055 boron/epoxy (0°-90° crossply)	A1-71
REFERENCES	A1-72

Polymer Matrix Composites: Materials Properties

CMH-17

COMPOSITE MATERIALS HANDBOOK



WICHITA STATE
UNIVERSITY



**NOT MEASUREMENT
SENSITIVE**

CMH-17-2H
Volume 2 of 6

FEBRUARY 2018

SUPERSEDING
CMH-17-2G
Volume 2 of 6
17 JUNE 2012

COMPOSITE MATERIALS HANDBOOK

POLYMER MATRIX COMPOSITES: MATERIALS PROPERTIES

VOLUME 2. Rev. H/Part B



CMH-17

COMPOSITE MATERIALS HANDBOOK

ISBN-Print 978-0-7680-9481-7

Copyright 2018 - Composite Materials Handbook – 17 (CMH-17). All rights reserved. Unauthorized duplication or distribution may violate the Copyright Laws of the United States and of other jurisdictions

TABLE OF CONTENTS

	Page
Foreword	ii
Summary of Changes	v
 PART A	
Chapter 1 General Information	1-1
Chapter 2A Carbon Fiber Composites	2A-1
Appendix A1. MIL-HDBK-17A Data.....	A1-1
 PART B	
Chapter 2B Carbon Fiber Composites	2B-1
Chapter 3 Boron Fiber Composites	3-1
Chapter 4 Glass Fiber Composites	4-1
Chapter 5 Quartz Fiber Composites	5-1

SUMMARY OF CHANGES

Chapter	Section [old section #]	Title	Change type
2		<u>Carbon Fiber Properties</u>	
	2.3.2.15 [2.2.2.4]	AS4C 3k/HTM45 8-Harness Satin Fabric	Reorganization
	2.3.2.16 [2.2.2.5]	AS4C 3k/HTM45 Plain Weave Fabric	Reorganization
4		<u>Glass Fiber Composites</u>	
	4.2.1.1	S-2 Glass/BT250E-6 Unidirectional Tape	New/St. Paul (8/2016)
	4.2.2.2	6781 S-2 Glass/MTM45-1 8-Harness Satin Weave Fabric	New/Miami (8/2014)
	4.2.2.3	E-Glass 7781/MTM45-1 8-Harness Satin Weave Fabric	New/Supplemental YPs (3/2015)